

HS KLEBTEC

Hand Gun- Hose Assembly



BEAD APPLICATION
HPD / DSH

SPRAY APPLICATION
HPS / DSHS

Operator Comfort-
HPD HPS
fatigue free

HAND - GUN

HAND APPLICATION FOR HOT MELT GLUE

- reliable
- practical
- swivel gun head
- compact

HAND GUN- HOSE ASSEMBLIES

HPD / DSH
BEAD APPLICATION

HPS/DSHS
SPRAY APPLICATION

Features of the gun/hose-assembly

- Lightweight and flexible hose
- Safe and easy connections
- Interchangeable components suit all models
- High grade thermocouple
- Durable, lightweight gun (400 grams)
- "Pump on Demand" gun trigger
- Light trigger action for continuous gluing
- 360 degree swivel attachment
- Well insulated handle
- Various nozzles available

Features of the spray gun

- Self-cleaning spray nozzle
- Spray air warmed to retain hot melt liquidity
- Air and electrical supply does not restrict the 360 degree gun swivel action.

Technical Data

Weight of gun	400 g
Temperature range	100°C - 200°C
Option	up to 230 °C
Hose and gun capacity	250 watts / 48 volts
Standard length of hose	2,5 m
Other lengths on request	
Hose diameter	35 mm
Standard nozzle bead, diam.	1,5 mm
Standard nozzle spray, diam.	1,0 mm
Other nozzles on request	

HAND APPLICATOR FOR HOT MELT GLUE



lightweight
handy
flexible



Various application patterns are possible.

We reserve the right to alter specifications without notice.

HS KLEBTEC

The hand guns are easy to operate, lightweight and swivel mounted, to a slim, flexible well insulated hose, which enables operators to reach awkward areas. They are designed for continuous use and operate at a safe voltage of 48 volts AC.

A variety of applicator nozzles are available to produce different applications such as bead or swirl spray patterns.

HS KLEBTEC GmbH

Zum Brauteich 22
07613 Rudelsdorf
Germany

Tel. ++49 (0)36691-43764

Fax ++49 (0)36691-54228

e-mail hs.klebtec@t-online.de